

FOR CONCRETE, STEEL

EAP-LOCK

Detachable single anchor point



The LOCK-13 single anchor point from INNOTECH with the detachable, rotating anchorage eye secures 2 people (including 1 person for the provision of first-aid) with personal protective equipment. The matching LOCK-11 receptacle sleeve from

INNOTECH® is permanently attached to the masonry, and has a protective cap which suitably covers the single anchor point when not in use. Inspection was performed both statically and dynamically on the original substructure.

- detachable anchor point with rotating anchorage eye
- for concrete, and steel constructions
- optimised safety locking

- architecturally unobtrusive (detachable)
- Certification to:
EN 795:2012 TYPE B
CEN/TS 16415:2013



SINGLE ANCHOR POINT

EAP | SINGLE ANCHOR POINT

LOCK-11

RECEPTACLE SLEEVE FOR EAP-LOCK-13 (EN 795 B, DIBT)

Substructure: Concrete (at least C20/25), red brick, steel construction

Usable thread lengths: 100/200/300/400/500 mm

Thread: M22

Drill hole: Ø 24 mm (drilling depth at least 110 mm)

Accessories: 2x replacement caps in red and white

Material: stainless steel (AISI 304) with M10 inner thread, suitable for the pull-out



LOCK-12

END CAP FOR EAP-LOCK-11 IN RED OR WHITE



LOCK-13

SINGLE ANCHOR POINT, DETACHABLE, ROTATING ANCHORAGE EYE (EN 795 B)

Substructure: Receptacle sleeve EAP-LOCK-11

Material: stainless steel (AISI 304), aluminium, brass

Increased safety thanks to innovative locking system



DETACHABLE ANCHOR POINT WITH ROTATING ANCHORAGE EYE

EAP-LOCK